



TECHNICAL DATA SHEET

SOIL POWER PRO 5W/30 SN/CF DPF

PRODUCT DESCRIPTION

SOIL POWER PRO 5W/30 SN/CF DPF is a high performance synthetic motor oil that meets the requirements of the new generation of engines. It has been developed to maintain and extend the efficiency of emission systems in both diesel and gasoline passenger cars and has been fully compatible with the diesel particulate filter (DPF) and three-way catalytic converter (TWC).

PROPERTIES

- New additive technology ensures excellent protection against engine wear even in the toughest operating conditions.
- Diesel particulate filters help to reduce the accumulation of particulate and wear of catalytic converters in gasoline vehicles.
- It provides fuel economy thanks to its improved anti-friction feature.
- Superior thermal and oxidation stability helps to reduce oil ageing by providing longer oil change intervals.
- The active cleaning feature controls the formation of sludge and keeps the engine clean and reduces maintenance costs.
- Quick starting in cold weather and very fast protection help to extend engine life.

APPROVAL AND SPECIFICATIONS

•API SN/CF• ACEA C3• MB 229.31, MB 229.51• Ford WSS M2C 913D• BMW LL-04• VW 504 00/ 507 00• GM Dexos 2

TECHNICAL SPECIFICATIONS

TEST	UNIT	METHOD	TYPICAL VALUES
K. Viscosity, @ 100 °C	cSt	ASTM D 445	11.8
Viscosity Index	-	ASTM D 2270	167
Flash Point	°C	ASTM D 92	225
Pour Point	°C	ASTM D 97	-39

*The above values may vary slightly according to production.

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

It should not be in contact with the skin and eyes, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, should be washed with plenty of water and medical attention should be sought if necessary. If swallowed, the victim should not be induced vomiting and immediate medical attention should be sought. If vapor is inhaled, plenty of breath should be taken in fresh air and, if necessary, medical attention should be sought. Used oils should not be disposed to garbage, sewage or receiving environment, they should be collected in waste oil collection containers complying with the legislation, and delivered to the manufacturer or licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in stove and boilers. It should be kept out of the reach of children. Empty containers should not be thrown to the garbage or left in the receiving environment, they should be delivered to licensed recycling companies.

For detailed information, you can review the "Material Safety Data Sheet".

STORAGE CONDITIONS

Packages should not be exposed to long-term and direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. It is the sole responsibility of the user to use this product for its intended purpose and to comply with applicable laws and regulations. ALKİM PETROKİMYA SAN ve TİC A.Ş. cannot be held responsible for any damage or loss that may result from the abnormal or improper use of the product, or for the dangers in the structure of the product and for its consequences.