



## TECHNICAL DATA SHEET

### *SOIL POWERSHIFT ATF DEXRON II*

#### PRODUCT DESCRIPTION

SOIL POWERSHIFT ATF DEXRON II is a high quality automatic transmission oil prepared with very well refined base oils. It is used in hydraulic steering systems and automatic transmissions of vehicles that require GM Dexron II and Mercon performance levels. It is also used safely in passenger cars, steering gears of heavy vehicles, automatic transmissions and transmissions.

#### PROPERTIES

- Longer life thanks to its high oxidation resistance.
- It provides smooth and smooth shifting thanks to its very good fluidity at low temperatures.
- It provides excellent lubrication by forming a very good film layer, prevents wear on gears and bearings.
- By distributing the heat very well, it provides lossless and trouble-free operation in automatic transmissions.
- Thanks to its high viscosity index, it minimizes friction in a wide operating temperature range.

#### APPROVAL AND SPECIFICATIONS

• GM Dexron II D • Caterpillar TO-2 • Allison C-4 • Hagglunds Denison HF-0 • MB Page 236.7/236.5 • MAN 339 V1, Z1 • Voith G607

#### TECHNICAL SPECIFICATIONS

TEST	UNIT	METHOD	TYPICAL VALUES
K. Viscosity, @ 100 °C	cSt	ASTM D 445	7
Viscosity Index	-	ASTM D 2270	137
Flash Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-41

\* The above values may vary slightly according to production.

#### HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

It should not be in contact with the skin and eyes, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, should be washed with plenty of water and medical attention should be sought if necessary. If swallowed, the victim should not be induced vomiting and immediate medical attention should be sought. If vapor is inhaled, plenty of breath should be taken in fresh air and, if necessary, medical attention should be sought. Used oils should not be disposed to garbage, sewage or receiving environment, they should be collected in waste oil collection containers complying with the legislation, and delivered to the manufacturer or licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in stove and boilers. It should be kept out of the reach of children. Empty containers should not be thrown to the garbage or left in the receiving environment, they should be delivered to licensed recycling companies.

For detailed information, you can review the "Material Safety Data Sheet".

#### STORAGE CONDITIONS

Packages should not be exposed to long-term and direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. It is the sole responsibility of the user to use this product for its intended purpose and to comply with applicable laws and regulations. ALKİM PETROKİMYA SAN ve TİC A.Ş. cannot be held responsible for any damage or loss that may result from the abnormal or improper use of the product, or for the dangers in the structure of the product and for its consequences.