



TECHNICAL DATA SHEET

SOIL RACING 4T 10W/40 SL

PRODUCT DESCRIPTION

SOIL RACING 4T 10W/40 SL is semi synthetic engine oil that is developed for four-stroke motorcycle engines. It provides protection against abrasion by forming protective film coating on motor parts. It prevents rust, corrosion and foam formations thanks to high quality additives it contains. It extends working life of engine and oil and increases their performances. It substantially reduces adverse effects resulting from long time and high speed usages, heavy urban traffic, sudden accelerations, brake or short time usages. It is appropriate to be used in motorcycles with wet clutch coupling.

PROPERTIES

- It provides excellent engine performance in air and water cooling engines even at high temperatures.
- It prevents oil film from tearing by keeping oil viscosity under control even under harsh conditions because of its high and stable viscosity index.
- Oil's life span is long because of its high resistance against abrasions, rust and corrosion.
- It provides low oil consumption and long oil change period.
- It provides sustainable maximum engine performance through its special formulation that can release power.

APPROVAL AND SPECIFICATIONS

- API SL • JASO MA2

TECHNICAL SPECIFICATIONS

| TEST | UNIT | METHOD | TYPICAL VALUES |
|-------------------------------|------|-------------|----------------|
| K. Viscosity, @ 100 °C | cSt | ASTM D 445 | 14.4 |
| Viscosity Index | - | ASTM D 2270 | 146 |
| Flash Point | °C | ASTM D 92 | 220 |
| Pour Point | °C | ASTM D 97 | -30 |

* The above values may vary slightly according to production.

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

It should not be in contact with the skin and eyes, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, should be washed with plenty of water and medical attention should be sought if necessary. If swallowed, the victim should not be induced vomiting and immediate medical attention should be sought. If vapor is inhaled, plenty of breath should be taken in fresh air and, if necessary, medical attention should be sought. Used oils should not be disposed to garbage, sewage or receiving environment, they should be collected in waste oil collection containers complying with the legislation, and delivered to the manufacturer or licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in stove and boilers. It should be kept out of the reach of children. Empty containers should not be thrown to the garbage or left in the receiving environment, they should be delivered to licensed recycling companies. For detailed information, you can review the "Material Safety Data Sheet".

STORAGE CONDITIONS

Packages should not be exposed to long-term and direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 °C. It is the sole responsibility of the user to use this product for its intended purpose and to comply with applicable laws and regulations. ALKİM PETROKİMYA SAN ve TİC A.Ş. cannot be held responsible for any damage or loss that may result from the abnormal or improper use of the product, or for the dangers in the structure of the product and for its consequences.